

VIT DRACE ALI DRACE

SIZES & SPECS SHEET



Species	Radiata Pine
Durability	Untreated or T3+ Treatment T3+ is CodeMark certified: H3 equivalent [AU] & H3.2 equivalent [NZ].
Width	200mm, 240mm, 300mm, 360mm, 400mm, 450mm, 500mm, 550mm, 600mm
Height	2440mm, 2590mm, 2740mm, 3000mm
Compatible Frame Depth	90mm
Tie-Down Bracket	Multinail Stronghold tie-down brackets (STD320)
Joint Group	JD5

XLT PORTAL ALI PORTAL

SIZES & SPECS SHEET



	2 x Columns	1 x Beam
XLT Portal 300	300mm Width, 90mm Thickness	300mm Width, 90mm Thickness
XLT Portal 360	360mm Width, 90mm Thickness	360mm Width, 90mm Thickness
XLT Portal 400	400mm Width, 90mm Thickness	400mm Width, 90mm Thickness

Kits Include:

The system is available in three (3) standard sizes – XLT Portal 300, 360, and 400 – to suit a range of span and load requirements.

- XLT Brace and XLT Portal (2x columns + 1x beam)
- Multinail steel knee joint connectors (8x plates)
- Multinail column base tie-down brackets (STD320) (4x brackets).